



SAFETY DATA SHEET

Rigby Taylor Premier HG 3-3-32 20kg

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Rigby Taylor Premier HG 3-3-32 20kg
Product number	I1909
REACH registration notes	Exempt from REACH registration according to Regulation (EC) No. 1907/2006 (REACH) This product contains a SVHC (Substance of Very High Concern) that is on the REACH Regulation (EC 1907/2006) Candidate List

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Fertiliser
------------------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	Rigby Taylor Ltd Suite 16 Rivington House Horwich Loco Industrial Estate Horwich Bolton BL6 5UE +44 (0) 800 424919 +44 (0) 1204 677715 info@rigbytaylor.com
-----------------	---

1.4. Emergency telephone number

Emergency telephone	+44 (0) 1204 677777 8am - 5pm Mon - Fri
----------------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards	Not Classified
Health hazards	Eye Irrit. 2 - H319
Environmental hazards	Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word	Warning
Hazard statements	H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.

Rigby Taylor Premier HG 3-3-32 20kg

Precautionary statements	P264 Wash contaminated skin thoroughly after handling.
	P273 Avoid release to the environment.
	P280 Wear protective gloves/protective clothing/eye protection/face protection.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with national regulations.	

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SSP Single Superphosphate 10-30%		
CAS number: 8011-76-5	EC number: 232-379-5	REACH registration number: 01-2119488967-11-XXXX
Classification Eye Irrit. 2 - H319	Classification (67/548/EEC or 1999/45/EC) Xi; R41	
Copper Sulphate <1%		
CAS number: 7758-99-8	EC number: 231-847-6	M factor (Acute) = 10
M factor (Chronic) = 10		
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC or 1999/45/EC) Xn; R22. Xi; R36/38. N; R50/53	
Boric acid (boron) <1%		
CAS number: 10043-35-3	EC number: 233-139-2	REACH registration number: 01-2119486683-25-XXXX
Classification Repr. 1B - H360FD	Classification (67/548/EEC or 1999/45/EC) Repr. Cat. 1 R60, R61	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Rigby Taylor Premier HG 3-3-32 20kg

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Get medical attention if symptoms are severe or persist.
Ingestion	Get medical attention if symptoms are severe or persist.
Skin contact	Wash skin thoroughly with soap and water or use an approved skin cleanser. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 10 minutes. Get medical attention if symptoms are severe or persist after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Dust in high concentrations may irritate the respiratory system.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	Skin irritation should not occur when used as recommended.
Eye contact	Prolonged or repeated exposure may cause severe irritation. May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Not applicable.

5.2. Special hazards arising from the substance or mixture

Specific hazards	None known.
-------------------------	-------------

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
Special protective equipment for firefighters	Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid inhalation of dust and contact with skin and eyes. Use suitable respiratory protection if ventilation is inadequate. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Take care as floors and other surfaces may become slippery.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	The product is slowly degradable. May cause long lasting harmful effects to aquatic life. Avoid discharge to the aquatic environment. Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Rigby Taylor Premier HG 3-3-32 20kg

Methods for cleaning up Take care as floors and other surfaces may become slippery. Collect and dispose of spillage as indicated in Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read label before use. Wear appropriate clothing to prevent repeated or prolonged skin contact. Avoid inhalation of dust and contact with skin and eyes.

Advice on general occupational hygiene Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a dry place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ammonium Sulphate

Long-term exposure limit (8-hour TWA): LTEL 10Mg/m³

Manganese Sulphate Mono

Long-term exposure limit (8-hour TWA): WEL 0.5 mg/m³

Boric acid (boron)

Long-term exposure limit (8-hour TWA): 10 mg/m³

Sodium Molybdate

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL 10 mg/m³

WEL = Workplace Exposure Limit

Kali Vinasse Powder

DNEL Workers - Dermal; Long term systemic effects: 30 mg/kg/day
Workers - Inhalation; Long term systemic effects: 106 mg/m³

PNEC - Fresh water; 0.46 mg/l
- Marine water; 0.046 mg/l
- Intermittent release; 0.56 mg/l
- STP; 1 mg/l

Potash (CAS: 7447-40-7)

DNEL Workers - Dermal; Short term systemic effects: 580 mg/kg/day
Workers - Dermal; Long term systemic effects: 580 mg/kg/day
Workers - Inhalation; Short term systemic effects: 292 mg/m³
Workers - Inhalation; Long term systemic effects: 292 mg/m³

Rigby Taylor Premier HG 3-3-32 20kg

PNEC Industry - Fresh water; 0,047 mg/l
- Marine water; 0,047 mg/l

SSP Single Superphosphate (CAS: 8011-76-5)

DNEL Workers - Inhalation; Long term systemic effects: 3.1 mg/m³
Workers - Dermal; Long term systemic effects: 17.4 mg/kg/day
General population - Inhalation; Long term systemic effects: 0.9 mg/m³
General population - Oral; Long term systemic effects: 2.1 mg/kg/day
General population - Dermal; Long term systemic effects: 10.4 mg/kg/day

PNEC - Fresh water; 1.7 mg/l
- Marine water; 0.17 mg/m³
- Intermittent release; 17 mg/l
- STP; 10 mg/l

Copper Sulphate (CAS: 7758-99-8)

DNEL Industry - Oral; Long term systemic effects: 0.041 mg/kg/day
Industry - Oral; Short term systemic effects: 0.082 mg/kg/day

Zinc Sulphate Monohydrate (CAS: 7446-20-0)

DNEL Industry - Inhalation; Long term systemic effects: 1 mg/m³
Industry - Dermal; Long term systemic effects: 8.3 mg/kg/day
Consumer - Oral; Long term systemic effects: 0.83 mg/kg/day
Professional - Inhalation; Long term systemic effects: 1.3 mg/m³
Consumer - Dermal; Long term systemic effects: 8.3 mg/kg/day

PNEC - Fresh water; 0.0206 mg/l
- Marine water; 0.0061 mg/l
- Sediment (Freshwater); 235.6 mg/kg
- Sediment (Marinewater); 113 mg/kg
- Soil; 106.8 mg/kg
- STP; 0.0052 mg/l

Boric acid (boron) (CAS: 10043-35-3)

DNEL Industry - Dermal; Long term systemic effects: 68.6 mg/kg/day
Industry - Inhalation; Long term systemic effects: 1.45 mg/m³
Consumer - Oral; Long term systemic effects: 0.17 mg/kg/day
Consumer - Inhalation; Long term systemic effects: 0.97 mg/m³
Consumer - Oral; Short term systemic effects: 0.17 mg/kg/day
Consumer - Dermal; Long term systemic effects: 34.3 mg/kg/day

PNEC - Fresh water; 1.35 mg/l
- Marine water; 1.35 mg/l
- Intermittent release; 9.1 mg/l
- Sediment; 1.8 mg/kg
- Soil; 5.4 mg/kg
- STP; 1.75 mg/l

8.2. Exposure controls

Rigby Taylor Premier HG 3-3-32 20kg

Protective equipment



Appropriate engineering controls	All handling should only take place in well-ventilated areas.
Eye/face protection	Wear eye protection.
Hand protection	Wear protective gloves.
Other skin and body protection	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.
Respiratory protection	No specific recommendations.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Granules.
Colour	Beige. to Dark brown. or Black.
Odour	Mild.
Odour threshold	Not determined.
pH	Slightly Acidic
Melting point	Not relevant.
Initial boiling point and range	Not relevant.
Flash point	Not relevant.
Evaporation rate	Not relevant.
Flammability (solid, gas)	The product is not flammable.
Vapour pressure	Not relevant.
Vapour density	Not relevant.
Relative density	Not relevant.
Solubility(ies)	Not known.
Partition coefficient	Not known.
Auto-ignition temperature	Not relevant.
Decomposition Temperature	Not relevant.
Viscosity	Not relevant.
Explosive properties	Not relevant.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information	No information required.
--------------------------	--------------------------

Rigby Taylor Premier HG 3-3-32 20kg

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable when stored in a dry place.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition products None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) No specific test data are available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No specific test data are available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Irritation of eyes is assumed. In-vitro testing conducted on products with SSP Content <62%, 2015, Result: Reduced classification to Eye Irritant. Test Guideline OECD 438. This result is less severe than the harmonized classification for Super Phosphates as Eye Damage 1 H318.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro This substance has no evidence of mutagenic properties.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity - fertility Contains a small amount of Boron which is a SVHC and may damage fertility and may cause damage to the unborn child.

Rigby Taylor Premier HG 3-3-32 20kg

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Eye contact

The product is considered to be a low hazard under normal conditions of use. May cause eye irritation.

SECTION 12: Ecological Information

Ecotoxicity Contains Copper Sulphate Contains Manganese Sulphate Mono Harmful to aquatic life with long lasting effects.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is slowly degradable.

12.3. Bioaccumulative potential

Partition coefficient Not known.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not relevant.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Reuse or recycle products wherever possible. No specific disposal method required.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Rigby Taylor Premier HG 3-3-32 20kg

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	14/06/2016
Revision	2
Supersedes date	29/03/2016
SDS number	5276
Risk phrases in full	R8 Contact with combustible material may cause fire. R22 Harmful if swallowed. R36/38 Irritating to eyes and skin. R41 Risk of serious damage to eyes. R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R60 May impair fertility. R61 May cause harm to the unborn child.

Rigby Taylor Premier HG 3-3-32 20kg

Hazard statements in full

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H360FD May damage fertility. May damage the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.