

SAFETY DATA SHEET Rigby Taylor Proseed 8-12-8+1.8Mg+Zn 20kg

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Rigby Taylor Proseed 8-12-8+1.8Mg+Zn 20kg

Product number 13148

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fertiliser

1.3. Details of the supplier of the safety data sheet

Supplier Rigby Taylor Ltd

Suite 16 Rivington House Horwich Loco Industrial Estate

Horwich Bolton BL6 5UE

+44 (0) 800 424919 +44 (0) 1204 677715 info@rigbytaylor.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1204 677777 8am - 5pm Mon - Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Rigby Taylor Proseed 8-12-8+1.8Mg+Zn 20kg

Precautionary statements P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SSP Single Superphosphate 10-30%

CAS number: 8011-76-5 EC number: 232-379-5 REACH registration number: 01-

2119488967-11-XXXX

Classification (67/548/EEC or 1999/45/EC)

Eye Irrit. 2 - H319 Xi; R41

Zinc Sulphate Monohydrate 1-5%

CAS number: 7446-20-0 EC number: 231-793-3 REACH registration number: 01-

2119474684-27-XXXX

M factor (Acute) = 1 M factor (Chronic) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn; R22. Xi; R41. N; R50/53

Eye Dam. 1 - H318 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Get medical attention if symptoms are severe or persist.

Ingestion Get medical attention if symptoms are severe or persist.

Skin contact Wash skin thoroughly with soap and water or use an approved skin cleanser. Get medical

attention if symptoms are severe or persist after washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Continue to rinse for at least 10 minutes. Get medical attention if symptoms

are severe or persist after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Dust in high concentrations may irritate the respiratory system.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Skin irritation should not occur when used as recommended.

Eye contact Prolonged or repeated exposure may cause severe irritation. May cause severe eye irritation.

Rigby Taylor Proseed 8-12-8+1.8Mg+Zn 20kg

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Not applicable.

5.2. Special hazards arising from the substance or mixture

Specific hazards None known.

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of dust and contact with skin and eyes. Use suitable respiratory protection if

ventilation is inadequate. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Take care as floors and other

surfaces may become slippery.

6.2. Environmental precautions

Environmental precautions The product is slowly degradable. Harmful to aquatic life with long lasting effects. Avoid the

spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Take care as floors and other surfaces may become slippery. Collect and dispose of spillage

as indicated in Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read label before use. Wear appropriate clothing to prevent repeated or prolonged skin

contact. Avoid inhalation of dust and contact with skin and eyes.

Advice on general occupational hygiene

Wash hands thoroughly after handling. Wash at the end of each work shift and before eating,

smoking and using the toilet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a dry place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Rigby Taylor Proseed 8-12-8+1.8Mg+Zn 20kg

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ammonium Sulphate

Long-term exposure limit (8-hour TWA): LTEL 10Mg/m3

Dolomite

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

WEL = Workplace Exposure Limit

SSP Single Superphosphate (CAS: 8011-76-5)

DNEL Workers - Inhalation; Long term systemic effects: 3.1 mg/m³

Workers - Dermal; Long term systemic effects: 17.4 mg/kg/day

General population - Inhalation; Long term systemic effects: 0.9 mg/m³ General population - Oral; Long term systemic effects: 2.1 mg/kg/day General population - Dermal; Long term systemic effects: 10.4 mg/kg/day

PNEC - Fresh water; 1.7 mg/l

Marine water; 0.17 mg/m³
Intermittent release; 17 mg/l

- STP; 10 mg/l

DAP Granular (CAS: 7783-28-0)

DNEL Workers - Inhalation; Long term systemic effects: 6.1 mg/m³

PNEC - Fresh water; 1.7 mg/l

Potash (CAS: 7447-40-7)

DNEL Workers - Dermal; Short term systemic effects: 580 mg/kg/day

Workers - Dermal; Long term systemic effects: 580 mg/kg/day Workers - Inhalation; Short term systemic effects: 292 mg/m³ Workers - Inhalation; Long term systemic effects: 292 mg/m³

PNEC Industry - Fresh water; 0,047 mg/l

- Marine water; 0,047 mg/l

Zinc Sulphate Monohydrate (CAS: 7446-20-0)

DNEL Industry - Inhalation; Long term systemic effects: 1 mg/m³

Industry - Dermal; Long term systemic effects: 8.3 mg/kg/day Consumer - Oral; Long term systemic effects: 0.83 mg/kg/day Professional - Inhalation; Long term systemic effects: 1.3 mg/m³ Consumer - Dermal; Long term systemic effects: 8.3 mg/kg/day

PNEC - Fresh water; 0.0206 mg/l

- Marine water; 0.0061 mg/l

Sediment (Freshwater); 235.6 mg/kgSediment (Marinewater); 113 mg/kg

Soil; 106.8 mg/kgSTP; 0.0052 mg/l

8.2. Exposure controls

Rigby Taylor Proseed 8-12-8+1.8Mg+Zn 20kg

Protective equipment





Appropriate engineering

controls

All handling should only take place in well-ventilated areas.

Eye/face protection Wear eye protection.

Hand protection Wear protective gloves.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

Respiratory protection No specific recommendations.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Granules.

Colour Beige. to Dark brown. or Black.

Odour Mild.

Odour threshold Not determined.

pH Slightly Acidic

Melting point Not relevant.

Initial boiling point and range Not relevant.

Flash point Not relevant.

Evaporation rate Not relevant.

Flammability (solid, gas) The product is not flammable.

Vapour pressure Not relevant.

Vapour density Not relevant.

Relative density Not relevant.

Solubility(ies) Not known.

Partition coefficient Not known.

Auto-ignition temperature Not relevant.

Decomposition Temperature Not relevant.

Viscosity Not relevant.

Explosive properties Not relevant.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

Rigby Taylor Proseed 8-12-8+1.8Mg+Zn 20kg

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable when stored in a dry place.

10.3. Possibility of hazardous reactions

Possibility of hazardous

No potentially hazardous reactions known.

reactions

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition

None known.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 40,139.86

Acute toxicity - dermal

Notes (dermal LD₅₀) No specific test data are available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritationBased on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Irritation of eyes is assumed. In-vitro testing conducted on products with SSP Content <62%,

2015, Result: Reduced classification to Eye Irritant. Test Guideline OECD 438. This result is less severe than the harmonized classification for Super Phosphates as Eye Damage 1 H318.

Respiratory sensitisation

Respiratory sensitisation No specific test data are available.

Skin sensitisation

Skin sensitisation Not determined.

Germ cell mutagenicity

Genotoxicity - in vitroThis substance has no evidence of mutagenic properties.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity - fertility Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposureNot classified as a specific target organ toxicant after a single exposure.

Rigby Taylor Proseed 8-12-8+1.8Mg+Zn 20kg

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Eye contact The product is considered to be a low hazard under normal conditions of use. May cause eye

irritation.

SECTION 12: Ecological Information

Ecotoxicity Contains Zinc Sulphate Mono May cause long lasting harmful effects to aquatic life. The

product contains substances which are toxic to aquatic organisms and which may cause long-

term adverse effects in the aquatic environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is slowly degradable.

12.3. Bioaccumulative potential

Partition coefficient Not known.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not relevant.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

Disposal methods Reuse or recycle products wherever possible. No specific disposal method required.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Rigby Taylor Proseed 8-12-8+1.8Mg+Zn 20kg

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 11/05/2016

Revision 1

SDS number 5535

Risk phrases in full R22 Harmful if swallowed.

R41 Risk of serious damage to eyes.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Hazard statements in full H302 Harmful if swallowed.

H318 Causes serious eye damage. H319 Causes serious eye irritation. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.