




329

Screwed flange, drilled, 4 holes

- Diameter of pitch circle and sealing face compatible to EN 1092-2 and DIN 2566.
- * 8 holes



EN	Dim. (inch)	PN	Black Code	Galvanised Code	SP	GP
-	½	PN 16	770 329 104	770 329 204	0	10
-	¾	PN 16	770 329 105	770 329 205	0	10
-	1	PN 16	770 329 106	770 329 206	0	5
-	1 ¼	PN 16	770 329 107	770 329 207	0	10
-	1 ½	PN 16	770 329 108	770 329 208	0	10
-	2	PN 16	770 329 109	770 329 209	0	8
-	2 ½	PN 16	770 329 110	770 329 210	0	6
-	3	PN 10	770 329 111	770 329 211	0	4
* -	3	PN 16	770 329 115	770 329 215	0	4
* -	4	PN 16	770 329 112	770 329 212	0	3

EN	Dim. (inch)	PN	a (mm)	b (mm)	d (mm)	k (mm)	z (mm)	H (mm)	D (mm)
-	½	PN 16	35	14	14	65	7	20	95
-	¾	PN 16	45	16	14	75	9	24	105
-	1	PN 16	52	17	14	85	7	24	115
-	1 ¼	PN 16	60	17	19	100	7	26	140
-	1 ½	PN 16	72	13	19	110	8	26	150
-	2	PN 16	87	16	19	125	5	29	165
-	2 ½	PN 16	100	16	19	145	5	32	185
-	3	PN 10	115	18	19	160	6	36	200
* -	3	PN 16	115	18	19	160	6	36	200
* -	4	PN 16	140	20	19	180	2	38	220

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>